



CAN MUD
SUSTAINABLE DRILLING FLUID SYSTEM

Canadian Mud Corporation

1018 7th street S.W.
High River, AB, T1V 1A9

Canada

1 (403) 652-8778

www.canmud.ca



CAN-DRILL

DESCRIPTION

CAN-DRILL is a very high molecular weight powder polymer formulated to quickly increase the viscosity of your drilling fluid. This assists with the removal of cuttings by creating a high viscosity environment down the hole, while simultaneously acting as a powerful hole stabilizer.

APPLICATION

CAN-DRILL should be premixed with CAN-LUBE before introducing it to the water tank to create a high viscosity mud system. CAN-DRILL can be added to all products to be used as a viscosifier where more viscosity is required.

ENVIRONMENTAL BENEFITS

- Environmentally conscious
- Less water consumption
- Easier disposal
- Less waste
- Less CO2 emissions

ECONOMIC BENEFITS

- Increases productivity by reducing drag
- Reduces torque by keeping the hole clean
- Less dosage per mix, minimizing overall cost
- Extends bit life by keeping waterways clean
- Reduced cost per meter

**"I like to use CAN-DRILL as much as I can.
It is my all-around drilling fluid!"**
- Derek McDriller



5 STAR MUD SYSTEM IN 3 EASY STEPS! BASED ON A 1,000 LT MIXING TANK

1

Pour 1 liter of CAN-LUBE into an empty container.

2

Add 1 liter of CAN-DRILL to the CAN-LUBE and premix well. Add more CAN-DRILL if more viscosity is required.

3

Add the premixed combination of CAN-LUBE and polymer to your mixing tank, then add 0.5 - 1 liter of CAN-CLAY to the mix if needed. Finish filling with water while continuing to mix. For best results, mix for 10 Minutes if possible, this should result in a viscosity of 40-45 seconds.