



**CAN MUD**  
SUSTAINABLE DRILLING FLUID SYSTEM

**Canadian Mud Corporation**

1018 7th street S.W.  
High River, AB, T1V 1A9

Canada

1 (403) 652-8778

www.canmud.ca



# CAN-LUBE

## DESCRIPTION

CAN-LUBE is our proprietary water-soluble drilling lubricant that has been formulated specifically for all water-based mud systems. Because of its high polarity, and its ability to stick on the steel, this vegetable oil-based lubricant is a great solution for reducing torque, while protecting the drill string and all down hole tooling. CAN-LUBE also enhances the performance of our powdered polymers, making them easier to mix and allowing them to create longer chains with greater strength.

## APPLICATION

CAN-LUBE is a high-performance environmentally conscious torque reducer. It can be added directly down the hole into the annular space, mixed with water in your tank or premixed with all powdered polymers to be used as a mud system.

## ENVIRONMENTAL BENEFITS

- Sustainable Vegetable base
- Environmentally conscious
- Easier disposal
- Less waste
- Less CO2 emissions

## ECONOMIC BENEFITS

- Increase penetration rates
- Reduces down-the-hole torque
- Extends bit life
- Prevents hole deviation and getting stuck
- Protects against premature rust and wear, specifically on drill rods, casing, and wire-line cable

**"I mix CAN-LUBE with everything!"**  
- Derek McDriller



## 5 STAR MUD SYSTEM IN 3 EASY STEPS! BASED ON A 1,000 LT MIXING TANK

**1**

Pour 1 liter of CAN-LUBE into an empty container.

**2**

Add 1 liter of CAN-DRILL, or CAN-CORE to the CAN-LUBE and premix well. Add CAN-DRILL if more viscosity is required.

**3**

Add the premixed combination of CAN-LUBE and polymer to your mixing tank, then add 0.5 - 1 liter of CAN-CLAY to the mix if needed. Finish filling with water while continuing to mix. For best results, mix for 10 Minutes if possible, this should result in a viscosity of 40-45 seconds.