



CAN MUD

SUSTAINABLE DRILLING FLUID SYSTEM

Canadian Mud Corporation

1018 7th street S.W.
High River, AB, T1V 1A9
Canada
1 (403) 652-8778
www.canmud.ca



CAN-CLAY

MULTI-USE CLAY INHIBITOR

DESCRIPTION

CAN-CLAY is a high-performance liquid friction reducer, also known as clay inhibitor. Use **CAN-CLAY** in very high water-sensitive clay formations to prevent the formation of mud rings and getting stuck down-the-hole.

APPLICATION

CAN-CLAY mixes very quickly and should be added directly into the mixing tank. Add **CAN-CLAY** to your mixing system as the last product for maximum efficiency. Start with 0.5 - 1 litre for every 1000 litres of fluid and adjust if necessary. It is crucial to continue adding **CAN-CLAY** once you are clear of clay zones, as reactive clays need to be treated from the top of the hole to the bottom.

ECONOMIC BENEFITS

- Increases ROP in soft formations
- Reduces torque by preventing mud rings
- Extends bit life by keeping waterways clean
- Less dosage per mix, minimizing overall cost
- Reduced cost per meter

ENVIRONMENTAL BENEFITS

- Environmentally conscious
- Less water consumption
- Easier disposal
- Less waste
- Less CO2 emissions



"I like to use **CAN-CLAY** as a preventive solution in unknown ground formations or when geologists indicate the presence of clays!" - Derek McDriller

