



CAN MUD

SUSTAINABLE DRILLING FLUID SYSTEM

Canadian Mud Corporation
1018 7th street S.W.
High River, AB, T1V 1A9
Canada
1 (403) 652-8778
www.canmud.ca



CAN-CORE

CORE RECOVERY MADE EASY

DESCRIPTION

CAN-CORE is a unique and powerful blend of powdered polymers formulated specifically to maximize core recovery in the most challenging ground conditions, such as sand and gravel. **CAN-CORE** also provides superior hole stabilization, preventing holes from collapsing during drilling operations. Unlike Bentonite, **CAN-CORE** penetrates the formation and strengthens it from the inside out, creating a protective film that maintains the integrity of the core sample and your borehole wall. **CAN-CORE** is a great alternative to Bentonite, reducing mixing time, transportation costs, and eliminating associated health hazards.

APPLICATION

CAN-CORE should be premixed with **CAN-LUBE** before introducing it to the water tank to create a high viscosity mud system. If more viscosity is required, add **CAN-DRILL** to your mud system.

ECONOMIC BENEFITS

- Increases productivity by getting more core in the box
- Less dosage per mix, minimizing overall cost
- Replaces Bentonite, reducing transportation and disposal costs
- Reduced cost per meter

ENVIRONMENTAL BENEFITS

- Environmentally conscious
- Less water consumption
- Easier disposal
- Less waste
- Less CO2 emissions

5 STAR MUD SYSTEM IN 3 EASY STEPS! BASED ON A 1,000 LT MIXING TANK

- 1** Pour 1 liter of **CAN-LUBE** into an empty container.
- 2** Add 1 liter of **CAN-CORE** to the **CAN-LUBE** and premix well. Add **CAN-DRILL** if more viscosity is required.
- 3** Add the premixed combination of **CAN-LUBE** and polymer to your mixing tank, then add 0.5 - 1 liter of **CAN-CLAY** to the mix if needed. Finish filling with water while continuing to mix. Mixing the full tank for 10 Minutes should result in a viscosity of 42-60 seconds.

"I like to use **CAN-CORE** to recover 100% core, even in the most difficult ground conditions!"
- Derek McDriller

