



CAN MUD

SUSTAINABLE DRILLING FLUID SYSTEM

Canadian Mud Corporation
1018 7th street S.W.
High River, AB, T1V 1A9
Canada
1 (403) 652-8778
www.canmud.ca



CAN-DRILL

MAXIMUM VISCOSITY

DESCRIPTION

CAN-DRILL is a very high molecular weight powder polymer formulated to quickly increase the viscosity of your drilling fluid. This assists with the removal of cuttings by creating a high viscosity environment down the hole, while simultaneously acting as a powerful hole stabilizer.

APPLICATION

CAN-DRILL should be premixed with CAN-LUBE before introducing it to the water tank to create a high viscosity mud system. CAN-DRILL can be added to all products to be used as a viscosifier where more viscosity is required.

ECONOMIC BENEFITS

- Increases productivity by reducing drag
- Reduces torque by keeping the hole clean
- Less dosage per mix, minimizing overall cost
- Extends bit life by keeping waterways clean
- Reduced cost per meter

ENVIRONMENTAL BENEFITS

- Environmentally conscious
- Less water consumption
- Easier disposal
- Less waste
- Less CO2 emissions

5 STAR MUD SYSTEM IN 3 EASY STEPS! BASED ON A 1,000 LT MIXING TANK

- 1** Pour 1 liter of **CAN-LUBE** into an empty container.
- 2** Add 1 liter of **CAN-DRILL** to the **CAN-LUBE** and premix well. Add **CAN-DRILL** if more viscosity is required.
- 3** Add the premixed combination of **CAN-LUBE** and polymer to your mixing tank, then add 0.5 - 1 liter of **CAN-CLAY** to the mix if needed. Finish filling with water while continuing to mix. Mixing the full tank for 10 Minutes should result in a viscosity of 42-60 seconds.

"I use can-drill the most as I often encounter competent or semi-fractured formations. it carries its weight by lifting cuttings and keeping the hole stable!" - Derek McDriller

